How to Configure Single Inclinometer Mode

Last Modified on 01/15/2018 2:44 pm PST

This document will walk you through how to configure your software to use Single Inclinometer Mode for Range of Motion test.

Before you begin:

• When in Single Inclinometer Mode, you must use the "Main/Left" device. This is usually designated by a yellow circle on your device.

Setup > Settings > ROM

- Open the Setup menu
- Selecting Settings > ROM

Protocol	Setu	ID	Help			
Backup	Seu	Do	Doctor Information		A	
		Dat	tabase		uick Training	
		Cal	ibrate	•		
	Settings			•		General
		Rep	ports	→		Devices
		Lar	iguage			Pair Device \ Check Status
						VisionPort
						Static
						Dynamic
						Thermography
						ROM
						Quick Screen

Single Inclinometer Mode

In the ROM settings window, select which exams you would like to perform with Single Inclinometer Mode.

- Clinical Exam Tests launched via "Start an Exam"
- Quick Screen Exam Tests launched via the Quick Screen icon or 5/F5 key

ROM Setting X									
Verification Mode Rep Count MWA 3 3	Inclinometer Set Button Zero time (ms) 100- 2500ms Sensitivity:	OK Cancel							
Clinical Exam - Use single inclinometer Quick Screen Exam - Use single inclinometer									
✓ Use Enhanced and FlexUltra (tm):									

Perform a ROM test

Perform a ROM test to see the changes. You should only see one Inclinometer image or one of the images will be X'd out.